


Luminaire

Code AP55215
Name VECTOR 40 RECESSED 940 FL BR.SILVER

Measur.

Code FTS1900879
Name VECTOR 40 RECESSED 940 FL BR.SILVER

Luminaire Flux	625.96 lm	Luminaire Power	8.00 W	Efficacy	78.25 lm/W	Efficiency	100.00%
Lamps Flux	625.96 lm	Maximum value	5684.10 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	40 mm 33 mm	Height Height	105 mm 0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.000855 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.000207 m2	
Coordinate system Date Measurement Distance		CG 24-10-2017 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 625.96 lm	
LED Flux=906,8lm LED Power=8W Eff=69% EfcLed=113lm/W EfcLum=78lm/W CCT=4000K Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E. F UTE	99 --	100 --	100 --	100 --	D DIN 5040 B NBN	A60 BZ 1	



Luminaire

Code AP55215
Name VECTOR 40 RECESSED 940 FL BR.SILVER

Measurement


Code FTS1900879
Name VECTOR 40 RECESSED 940 FL BR.SILVER

Luminaire Flux	625.96 lm	Luminaire Power	8.00 W	Efficacy	78.25 lm/W	Efficiency	100.00%
Lamps Flux	625.96 lm	Maximum value	5684.10 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	40 mm	Height	105 mm		
Round Luminous Area		Diam.	33 mm	Height	0 mm		
Horizontal Luminous Area		0.000855 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000207 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		24-10-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		625.96 lm	
LED Flux=906,8lm LED Power=8W Eff=69% EfcLed=113lm/W EfcLum=78lm/W CCT=4000K Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.36	0.54	0.72	0.91	OC	0.18	0.36	0.54	0.72	0.91
OB	0.18	0.36	0.54	0.72	0.91	OD	0.18	0.36	0.54	0.72	0.91

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	3558.02	3012.70	894.21	195.14	26.81	4.77	1.94	0.56	0.00	0.00
OB	3558.02	3012.70	894.21	195.14	26.81	4.77	1.94	0.56	0.00	0.00
OC	3558.02	3012.70	894.21	195.14	26.81	4.77	1.94	0.56	0.00	0.00
OD	3558.02	3012.70	894.21	195.14	26.81	4.77	1.94	0.56	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=10.3°+10.3°	G=0.0
1.00	0.36	3558	2249		
2.00	0.72	890	562		
3.00	1.09	395	250		
4.00	1.45	222	141		
5.00	1.81	142	90		