

## Luminaire


Code BH09004+BH16104  
 Name A.39 SHARP D+IND 1184 HB 54 300K DM NRO + COVER 3X4 OPT. HB BLACK

## Measurement

Code FTS1900121-A  
 Name A.39 SHARP D+IND 1184 HB 54 300K DM NRO + COVER 3X4 OPT. HB BLACK

Luminaire Flux	5414 lm	Luminaire Power	64.0 W	Efficacy	84.594 lm/W	Efficiency	100.00%
Source Flux	5414 lm	Maximum value	618.18 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	444 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.016428 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.003974 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5414 lm	
LED Flux=6973lm LED Power=53W Eff=78% EfcLed=132lm/W EfcLum=85lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h							
C.I.E.	99 100 100 43 100			D DIN 5040	C62		
F UTE	--			B NBN	BZ 1		

1184mm x 40mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 56.80 %

DLOR 43.20 %

RN 56.80 %

